

A3 UV DTF Printer

EPSON 2H

6Pass: 8.5m/h



LF-720C

- 1. Label printing and lamination in one, with winding.fully automatic, efficient, and cost-effective
- 3.Bright colors, high color intensity, clear and realistic, and first-class printing quality
- 2. The application materials are very wide, with high flexibility. One label/logo can also be printed
- 4. 30cm Printing width , speed of 2.5 square meters/h, Easily handle big batch printing

集团总部:广州市开发区光谱西路3号皓叶国际

Group HQ.: The 1st Floor of R&D Bd. No.3 Guangpu
West Rd., Huangpu Zone, Guangzhou city, Guangdong Province PRC.
E-mail: Betty030318@126.com











UV DTF

UV DTF ab film

UV ink

Application

- 1. The crystal label is convenient to use, Stick and tearimmediately. Wide range of uses and can be iregularly shaped, not just flat plates can printed ,too
- 2.It has a very obvious advantage over ordinary label, with strong three-dimensional sense, high glosiness, rich and bright pattern colors, high glossiness, easy peel, and no residual glue left;
- 3.One label can also be printed, with a wide range of applications. t can be transferred to surfaces such as glass, ceramics , acrylic,wood, PvC boards, various metal plates, plastics, stones, etc.
- 4. The machine is automatic and convenient. one person be able to run many machines. saving abor. Compared to screen printing and transter printing using UV printing greatly reduces labor costs;
- 5.A more environmentaliv friendly process. compared to soivents and the unpieasant and pungent sme of screen printing. UV ink ereatly reduces polutioi

► PRODUCT PARAMETERS

d	Epson	
f heads	Dual heads	
:h	≤300mm	
	CMYK+white ink+Varnish	
e Meda	UV dtf ab film	
peed	6pass 2.5m²/h	
	UV ink	
y system	500ml ink bottle+white ink cir	culation+stirrin
are	Maintop/PhotoPrint	
ş system	Win7、Win10	
5	Curing of air-cooled UV lamp	
suction	Adjustable	
rface	Network interface	
unction	Automatic inductive winding	
ure and humidity	15 - 30°C 35-65%	
parameters	220V 500W 2.3A	
veight	Machine: 980*940*1224mm Package: 1450*900*711mm	N.W 145KG G.W 185KG
	d f heads th e Meda peed y system are g system g suction rface unction ture and humidity parameters weight	If heads Dual heads CMYK+white ink+Varnish CMYK+white ink+Varnish Peed Opass 2.5m²/h UV ink Sysystem Maintop/PhotoPrint Win7、Win10 Curing of air-cooled UV lamp Suction Adjustable Ifface Network interface unction Automatic inductive winding For the parameters Sysystem Machine: 980*940*1224mm

- Printing and laminating all in one machine
- Printing width 30cm
- Printing speed 6pass 8.5m/h

