

## 3H-i3200-U1 60cm UV DTF Printer

EPSON i3200-U1 3H

6Pass: 10m/h



- 1. Label printing and lamination in one, with winding.fully automatic, efficient, and cost-effective
- 3.Bright colors, high color intensity, clear and realistic, and first-class printing quality
- 2. The application materials are very wide, with high flexibility. One label/logo can also be printed
- 4. 60cm Printing width , speed of 6 square meters/h, Easily handle big batch printing

## 集团总部:广州市开发区光谱西路3号皓叶国际

Group HQ.: The 1st Floor of R&D Bd. No.3 Guangpu
West Rd., Huangpu Zone, Guangzhou city, Guangdong Province PRO
E-mail: Betty030318@126.com



皓叶国际集团荣誉出品 Honorably produced by Bright Leaf Intil Group









**UV DTF** 

UV DTF ab film

UV ink

Application

- 1. The crystal label is convenient to use, Stick and tearimmediately. Wide range of uses and can be iregularly shaped, not just flat plates can printed ,too
- 2.lt has a very obvious advantage over ordinary label, with strong three-dimensional sense, high glosiness, rich and bright pattern colors, high glossiness, easy peel, and no residual glue left;
- 3.One label can also be printed, with a wide range of applications. t can be transferred to surfaces such as glass, ceramics , acrylic,wood, PvC boards, various metal plates, plastics, stones, etc.
- 4. The machine is automatic and convenient. one person be able to run many machines. saving abor. Compared to screen printing and transter printing using UV printing greatly reduces labor costs;
- 5.A more environmentaliv friendly process. compared to soivents and the unpieasant and pungent sme of screen printing. UV ink ereatly reduces polutioi

## ► PRODUCT PARAMETERS

Print head	Epson-i3200
Number of heads	Three I3200 heads
Print width	≤600mm
Color	CMYK+white ink+Varnish
Applicable Meda	UV dtf ab film
Printing speed	6pass 6㎡/h 8pass 5㎡/h
Ink type	UV ink
Ink supply system	1L ink bottle+white ink circulation+stirring
Rip Software	Maintop/PhotoPrint
Operating system	Win7、Win10
Ink drying	Curing of air-cooled UV lamp
Platform suction	Adjustable
Print Interface	Network interface
Winding function	Automatic inductive winding
Temperature and humidity	15 - 30°C 35-65%
Electrical parameters	220V 1500W 6.8A
Size & weight	Machine: 1875*950*1594mm N.W 245KG Package: 2000*900*711mm G.W 305KG

- Printing and laminating all in one machine
- Printing width 60cm
- Printing speed 6pass10m/h



Three i3200 heads